

FIRENZE / FIRENZE LINEA

SPECIFICATION

Quality		FIRENZE / FIRENZE LINEA
Product definition		tufted loop pile
Gauge		1/10"
No. of tufts	ISO 1763	$\pm 164000/m^2$
Pile fibre		100% Solution dyed polyamide
Pile weight		550 gr/m ² $\pm 5\%$
Pile height	ISO 1766	3.50 mm $\pm 5\%$
Primary backing		PA/PES non-woven - Colback
Tile backing		Polyflex with Glass Fiber Scrim
Total thickness	ISO 1765	6.8 mm $\pm 5\%$
Total weight		4300 gr/m ² $\pm 7,5\%$
Tile size		50 x 50 cm ($\pm 19.7" \times 19.7"$)
Tiles per box		20

PERFORMANCE

Use classification	method en 1307	: 33
Castor chair test	EN 985	: A, continuous use
Abrasion	EN 1963	: pass
Vettermann test	ISO 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: 0.08 m ² K/W
Dimensional stability	EN 988	: pass

ELECTROSTATIC PROPERTIES

Walk on test	ISO 6356	: -0.1 kV
Horizontal electrical resistance	ISO CD 10965	: $3 \times 10^8 \Omega$
Vertical electrical resistance	ISO CD 10965	: $4 \times 10^{10} \Omega$
Static loading		: anti-static

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: B _{fl} - s1
Hot metal nut test	BS 4790	: Low Radius

COLOUR FASTNESS PROPERTIES


Light	ISO 105 B02	: > 5
Rubbing, dry	ISO 105 X12	: 5.0
Rubbing, wet	ISO 105 X12	: 5.0
Shampoo	BS 1006	: 5.0
Water	ISO 105 E01	: 4.5
Water stains	TNO W 6024	: 5.0

GENERAL

Recommended maintenance: Best results are obtained when cleaned with a dry shampoo method.

Pile direction: Directional arrows are printed on the back of each tile.
Best results are obtained when laid checkerboard.

Laying instructions: Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.



Specification in according EN 13