URBON-PREX

Precipitation sensor network and automatic weather station

Precipitation measurement stations (10x)

Precipitation sensor

1 1

- Weighing Rain Gauge

- Parameters measured: Cumulative precipitation, precipitation intensity, bucket content in real time and non real time

- Measurement technology: Weighing principle

- All-weather precipitation gauge without moving parts according to WMO guide line No. 8

Recordable precipitation: Liquid, solid, and mixed
Collecting area: 200 cm² / 400 cm²

- Recordable precipitation amount: 1500 mm / 750 mm

- Accuracy (at -25 ... +45 °C)

Amount ±0.1 mm or ±1 % of measured value

Intensity ±0.1 mm/min, ±6 mm/h or ±1 % of measured value

Resolution 0.01 mm, 0.01 mm/min or mm/h

- Measurement interval: 1 min

- Data transfer: 10 min

Data logger

- Data collection and transfer

- Updatable software

- Possibility to connect to the internet via WIFI and mobile internet (1 station have to connect to internet using mobile internet, the rest have to connect via WIFI)

- all the measured values have to be stored in the station, in case of data transfer errors it have to be collected from the stations

Water resistant instrument box Uninterruptible power supply

- The instrument have to operate from battery minimum 4 hours

Instrument mast

- 1 m height

- 8 station it have to tie down into the soil, 2 cases it have to be a tripod fixed to concrete slabs

Fence around instrument

- 1,5 m height

- 3 (4 site) or 4 (4 site) sided

Long range WIFI router

- 9 sites

- Distance to are cover up to 55 m

GSM modem

- 1 site

Complete automatic weather station (1x)

Sensors

- temperature

Accuracy +-0.2 °C - humidity

Accuracy +-5 %

wind

Accuracy +-0,5 m/s in case of wind speed and +- 5° in case of diection

precipitation

Same as the precipitation stations

- air pressure

Accuracy +-0,5 hPa

radiation

Accuracy +-20 W/m²

- Measurement 1 min

- Data transfer 10 min

- Measured parameters (in each 10 min):

minimum, maximum, mean value and the actual value at the end of the 10 min interval of temperature, humidity, wind speed, air pressure

sum and actual value at the end of the 10 min interval: radiation

sum: precipitatin

actual value at the end of the 10 min interval: wind direction

Data logger

Data collection and transfer

Updatable software

- Possibility to connect to the internet via mobile internet

- all the measured values have to be stored in the station, in case of data transfer errors it have to be collected from the stations Water resistant instrument box

Uninterruptible power supply

- The instrument have to operate from battery minimum 4 hours

Instrument mast

- 10-2 m height

Fence around instrument

1,5 m height

-fixed with wires (2 end points have to fixed into ground, 1 endpoint into a building wall near to station)

-wires have to protected with plastic or rubber cover in the lowest 2 m

GSM modem

Instrument installation

Sites are presented in the attached supplement

Stations and fence have to be deployed

Electricity cable have to be connected to the nearest possible connections. The cable have to placed in to cable channel in case of building walls or have to be placed 0.5 m depth into the soil.

Long range WIFI router have to be installed into suitable position.

Data collection software

It will be installed into a server located in the Department of Climatology and Landscape Ecology. The operation system is debian linux, MySQL is available.

The software stores the incoming data into MySQL database and into txt files.

The software have to move the daily txt files to archive directory

Operation of the data collection could be monitored with nohup, but the nohup out file have to be moved to archive in each day.

1 year for equipment limited warranty for 5 year for the operation of the system (including software errors and design failures)

Deadlines, Payment Production of the equipments 2018 October up to 60 000 EUR Deployment of equipment 2018 December up to 32 000 EUR